| | Project Name: _ | | | _ AIA#: | |
|----------|-----------------|-----------|---|---------|--|
| Model #: | | Location: | | | |
| _ | | | _ | | |



Countertop Induction Range

Energy efficient cooking

No open flames, portable, light weight, and stores away easily.





Model

☐ GIR18-C

Standard Features

- 1800W, 120V
- 7 power levels
- Touch pad controls and 4 digit LED display
- Digital timer
- Proper pan detection and automatic empty pan safety shut-off
- Temperature settings from 140°F-460°F
- Error code alert display
- Adjustable feet for leveling unit
- Attached 5½-foot power cord and NEMA 5-20P plug (Canada)
- Seamless stainless steel construction
- Durable ceramic cooktop
- Easy-to-clean controls and cooktop

Warranty

One year parts and labor

Applications

Omelets, eggs & bacon, seafood, poultry, burgers, delicate sauces, butter, chocolate, etc.

To select options see back

| Approved by: | Date: |
|--------------|-------|
| ., , | |



For Indoor Use Only

SPECIFICATIONS

- Seamless stainless steel construction
- Touch pad controls and 4 digit LED display
- Digital timer
- Proper pan detection and automatic empty pan safety shut-off
- Temperature settings from 140°F-460°F
- Error code alert display
- Adjustable foot for leveling unit
- Attached 5½-foot power cord and plug

| Model | Power Levels | Temp Settings | Cooking Surface | Electric | AMPs | Wattage | NEMA Plug Type |
|---------|--------------|---------------|-----------------|-----------|------|---------|----------------|
| GIR18-C | 7 | 140°F-460°F | 4.75" to 10.25" | 120V/60Hz | 15 | 1800 W | 5-15P (U.S.) 😲 |
| | | | | | | | 5-20P (Canada) |

IMPORTANT: PERSONS WITH PACEMAKERS

Persons with pacemakers should stay at least 3 feet away from the induction range.

When using the induction range with the general public, a pacemaker notice should be posted near the equipment in use.

STANDARD EQUIPMENT:

Auto pan detection: Range detects if proper cookware/pan is placed on cooktop.

Automatic shut-off: Automatically shuts off when timer runs to "0".

Over-heat protection: Unit senses when the pan overheats and when the electrical components overheat; the unit then shuts off.

Digital timer: Set timer from 0-180 minutes.

Bright LED display: Bright 4 digit LED display for easy viewing.

Suitable Pans:

Steel or cast iron, enameled cast iron, stainless steel and aluminum if marked "suitable for induction cooking", flat-bottom pans/pots with diameter of 12 to 26 cm or 4.75" to 10.25".

DIMENSIONS & SHIPPING INFORMATION

Carton reinforced for shipping. The weight and dimensions of reinforced carton are listed below and may vary from shipment to shipment.

| Model | Overall Dimensions | Net Weight | Shipping Dimensions | Shipping Weight |
|---------|-------------------------------|------------|---------------------------------|-----------------|
| GIR18-C | 16.75" L × 13" W × 4" H | 12.46 lbs. | 19" L × 15.25" W× 6" H | 15 lbs. |
| | (42.54 cm × 33 cm × 10.16 cm) | (5.65 kg) | (48.26 cm × 38.73 cm × 15.2 cm) | (6.8 kg) |

2153 Dryden Rd., Dayton, OH 45439 | 937-299-5493 | 800-347-5423 | Fax: 937-299-4147 | www.globefoodeguip.com