



MODELS

KGL-OF-(40, 50, 60)-S KGL-OF-(40, 50, 60)-R GRAB-N-GO LOW PROFILE CASE

CASE HOLDS 36°F TO 40°F • FORCED AIR REFRIGERATION • OPEN FRONT FRONT LOADING • LED LIGHTING IN CANOPY AND UNDER ALL SHELVES PULL DOWN NIGHT CURTAIN • CASES CAN BE MULTIPLEXED





SELF CONTAINED	Model	Width (inches)	Front Capacity Cu.ft	Electrical 115 Volts				Weight lbs		Crate Size (inches)		
				Compressor		Total	NEMA Plug	No	With	L″	w″	Н″
				H.P	F.L.A	Amps		Crate	Crate	-		
	KGL-OF-40-S	41	12.98	5/8	8.9	16.42	5-20P	357	507	43.8	34.5	67.8
	KGL-OF-50-S	50.2	16.21	3/4	16	24.00	Hard-wired	394	569	53	34.5	67.8
	KGL-OF-60-S	60.6	19.85	3/4	16	24.06	Hard-wired	454	653	63.5	34.5	67.8

оте		Width		115 Volts		Weight lbs		
	Model	(inches)	B.T.U	Total Amps	Nema Plug	No Crate	With Crate	
REMOT	KGL-OF-40-R	41	4125	0.40	Hard-wired	291	441	
	KGL-OF-50-R	50.2	50.2 4897 0.43		Hard-wired	317	491	
	KGL-OF-60-R	60.6	5141	0.49	Hard-wired	376	575	

STANDARD FEATURES

Silver colored PVC coated steel front panel Pull down night curtain CFC free injected foam insulation PVC coated steel gray interior Black steel kick plate Foamed polystyrene black end panels Tempered side glass Height adjustable shelves can be tilted Products stop on shelves Temperature and defrost regulated by a digital controller Digital thermometer Slide out condensing unit on self-contained units Removable condensate evaporating pan for easy cleaning on self contained units Cord and plug KGL-OF-40S only Leveling feet


OPTIONAL FEATURES

Stainless steel exterior and / or interior Other colors available Additional shelves Price tag molding Joining kit Partition or product dividers Condensate evaporating pan for remote cases Casters-add 4-3/8" to height Stainless steel legs are adjustable from 5-1/8" to 7-5/8" WARRANTY One year parts and labor with an additional four years on the compressor (part only)



3560 NW 56th St Fort Lauderdale, FL USA 33309 Tel: 786.600.4687 / Toll Free: 844.218.8477 / Fax: 786.661.4100

5659 Royalmount Ave. Montreal, QC, Canada H4P 2P9 Tel: 514.737.9701 / Toll Free: 888.275.4538 / Fax: 514.342.3854 Toll free: 877.453.8832 sales@mvpgroupcorp.com / mvpgroupcorp.com





NOTE

These cases are engineered to operate in locations not exceeding 75°F and 55% R.H. These cases are designed to operate using R452a refrigerant. Alternate refrigerants available by special order. O.A. length includes (2) ends at 1-1/2" each. Ventilation grills at front and back cannot be blocked. B.T.U.'s are calculated at 14°F (evaporator) and 90°F (ambient). Remote cases are provided with an expansion valve and a liquid solenoid for pump down cycle. On remote cases, if no floor drain is provided, a condensate evaporating pan must be ordered and 6.7 amps added to the amp load. Remote cases must be hard wired – no plugs.



Hydra - Kool is a registered trademark of MVP Group Corp. SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE