

HID540 - Touch-Free Ice & Water Dispenser

Nugget Ice Machine / Dispenser

The Meridian® Difference

Sanitation

- Touch-free, infrared dispensing of ice and water eliminates the need to physically touch the dispenser for more sanitary operation
- AgION® and other antimicrobial compounds are molded into key components to help inhibit the growth of microbes, bacteria, mold and algae
- Fully removable bin, spouts, air filter, sink, and grill allow for easy cleaning and maintenance
- Sealed refrigeration system minimizes outside airborne contamination
- Front accessible, removable air filter makes cleaning more convenient

Reliability & Ease of Use:

- Sealed, maintenance-free bearings reduce preventative maintenance and ensure maximum reliability
- Produces Scotsman's chewable H² Nugget Ice which is slow-melting and designed for reliable dispensing
- Space-maximizing design the industry's smallest operational footprint relative to capacity, featuring specially designed contoured sides for enhanced breathability
- SmoothStream™ water dispensing technology reduces splashing to keep the machine and surrounding areas clean
- Unit-specific QR code for guick access to service manuals and warranty history
- Durable stainless-steel evaporator and exterior panels, plus larger sink opening and dispensing area
- Enhanced service features Intuitive LED diagnostic lights reduce service time and convenient USB drive allows for fast software updates
- Industry-leading energy and water efficiency along with quieter operation





bearings ensure maximum reliability and contribute to a long machine life

HID540A-1 with optional KLP24A legs



Touch-free infrared sensor dispensing option, providing more sanitary operation



User controlled antimicrobial push-button dispensing option, providing quick and efficient operation

24 Hour Volume Production Air Cooled Water Cooled 70°F/21°C Air 90°F/32°C 70°F/21°C Air 90°F/32°C 50°F/10°C Water 70°F/21°C 50°F/10°C Water 70°F/21°C 500/227 365/166 500/227 400/181 1b/f/a 1b/f/a 1b/f/a

Specifications

1									Water Usage	
ı				Storage		Max. Fuse Size			Gallons/100 lb (liters/45.4 kg)	
ı		Condenser	11	Capacity		or HACR Circuit			Potable	Condenser
ı	Number	Unit	Method	lb/kg	Volts/Hz/Phase	Breaker (amps)	Amps	90°F(32°C)/70°F(21°C)	90°F(32°C)	/70°F(21°C)
ı	HID540A-1	Air	Touch-Free Sensor	40/18.1	115/60/1	15	Cord	5.50	12/45.5	-
ı	HID540AB-1	Air	Button Activated	40/18.1	115/60/1	15	Cord	5.50	12/45.5	-
ı	HID540AW-13	* Air	Touch-Free Sensor	40/18.1	115/60/1	15	Cord	5.50	12/45.5	-
ı	HID540W-1	Water	Touch-Free Sensor	40/18.1	115/60/1	15	Cord	4.30	12/45.5	120/454.3
V	HID540WB-1	Water	Button Activated	40/18.1	115/60/1	15	Cord	4.30	12/45.5	120/454.3

^{*}Wall mount configuration. Does not have or accept a drip tray. Unit designed to be installed over existing sink.








- 3 years parts and labor.
- 5 years parts on the compressor and condenser.
- Warranty valid in North, South & Central America for commercial installations.
- Contact factory for warranty in other regions.
- Residential Applications: 1 year parts and labor




- 101 Corporate Woods Parkway, Vernon Hills, IL 60061 •
- 1-800-SCOTSMAN Fax: 847-913-9844 www.scotsman-ice.com customer.relations@scotsman-ice.com •


Without Wall Mount: HID540A(B) & HID540W(B)

Installation Note: Allow 6" space at left, back and right side for ventilation and utility connections. All models include 7.5' power cord with NEMA 5-15P plug.




With Wall Mount: HID540AW





RIGHT SIDE VIEW





Dimensions (W x D x H):

HID540A(B)-1: 21.25" x 24.38" x 41" HID540AW-1: 23.25" x 24.38" x 41" HID540W(B)-1: 21.25" x 24.38" x 41"

Shipping Carton:

HID540A(B)-1: 24.25" x 27.13" x 47.5" HID540AW-1: 24.25" x 27.13" x 47.5" HID540W(B)-1: 24.25" x 27.13" x 47.5"

Shipping Weight: HID540A(B)-1: 215lb / 98kg

HID540AW-1: 220lb / 100kg HID540W(B)-1: 215lb / 98kg

BTUs per hour: 6,800

Refrigerant: R-404A

Accessories

Model Number	Description
KLP24A	4" Adjustable legs, box of 4, plastic with metallic foot.
HST21-A	Machine stand for HID525 and HID540, with locking reversible door and shelf.
HST21B-A	Machine stand for HID525 and HID540, basic version.

Scotsman recommends all ice machines have water filtration. See Scotsman water filter specification sheet for details.



Operating Requirements

Minimum	Maximum	
50°F (10°C)	100°F (38°C)	
40°F (4.4°C)	100°F (38°C)	
20 PSIG (1.4 bar)	80 PSIG (5.5 bar)	
-5%	+10%	
	50°F (10°C) 40°F (4.4°C) 20 PSIG (1.4 bar)	50°F (10°C) 100°F (38°C) 40°F (4.4°C) 100°F (38°C) 20 PSIG (1.4 bar) 80 PSIG (5.5 bar)

Specifications and design are subject to change without notice.

• 101 Corporate Woods Parkway, Vernon Hills, IL 60061

• 1-800-SCOTSMAN Fax: 847-913-9844

© 2021 Scotsman Ice Systems.

• www.scotsman-ice.com customer.relations@scotsman-ice.com



an Ali Group Company