

4184 E. Conant St. Long Beach, CA 90808 Tel. 310-900-1000 Fax. 310-900-1077 www.turboairinc.com

Draigat
Project :
1 101001

Model # : Item # :

Qty :

Underbar Equipment <u>Super Deluxe Series</u>

Model : TBC-36SD/SB-N6

Available W/H :

Approval :

Bottle Coolers

Patented Self-Cleaning Condenser



This product is equipped with a fine mesh filter to the front of the condenser to catch dust, and a rotating brush that moves up and down daily to remove excess buildup outward and away.





____ FEATURES & BENEFITS =___

Self-Cleaning Condenser

The accumulation of dust in the condenser can cause the failure or breakdown of refrigerators. Refrigerators run normally until they reach a certain level of accumulation. At some point, when they are over the limit, their performance drops quickly resulting in damage to, or disposal of the stored products inside. The Self-Cleaning Condenser device keeps the condenser clean and prevents system failure by automatically brushing daily.

Bigginal states (R-600a)

With innovative and eco-friendly technology, Turbo Air brings you hydrocarbon refrigerators designed to meet the new standards of the EPA and DOE in 2017. Hydrocarbon refrigerants do not deplete the ozone layer and have very low contribution to global warming (ODP-0, GWP-3).

Forced air cooling system

Positive guided forced air cooling system chills bottles on top first.

High-density polyurethane insulation

The entire cabinet structure is foamed-in-place using high density, CFC free polyurethane insulation.

Side mount compressor unit

Stainless steel cabinet construction

Super Deluxe (SD) models boast a stainless steel exterior (except galvanized steel back and bottom). SB models have an attractive wear-resistant black vinyl exterior. Heavy gauge stainless steel countertop and glide lids are perfect for sanitation and durability. The interior is stainless steel except galvanized steel top. Turbo Air Bottle Cooler model guarantees the utmost in cleanliness and long product life. It also adds a touch of style to the most refined setting.

- Adjustable, heavy duty, PE (polyethylene) coated dividers
- Rugged built-in removable bottle cap opener and cap catcher
- Huge capacity cooler cabinet requires only minimum floor space
- Refrigerator holds 33°F ~ 38°F for the best in beverage preservation

NATURAL Refrigerant	ISO 9001:2008	context of the second s	Intertek	3 YEAR	Compressor 5 YEAR WARRANTY (U.S.A cróy)
	a . 1				

Model	Sliding Door	CU./FT.	Capacity 12oz.btls. / 12oz.cans	# of Dividers	HP	AMPS	Crated Weight (lbs.)	$L \ge D^* \ge H^{\dagger}$ (inches)
TBC-36SD-N6	1	8.5	12 / 15 Cases‡		1/8	1.6	221	363/4 x 261/2 x 331/4
TBC-36SB-N6	1	8.5	12 / 15 Cases‡		1/8	1.6	221	363/4 x 261/2 x 331/4

* Depth does not include 2" for cap catcher or 2" for rear spacers. + Height does not include 5" for caster height. + Case capacity refers to 24 pack.

Bottle Coolers

(unit : inch)

Model : TBC-36SD/SB-N6

ELECTRICAL DATA						
Voltage	115/60/1					
Plug Type	(i) NEMA 5-15P					
Full Load Amperes	1.6					
Compressor HP	1/8					
Refrigerant	R-600a					
Cord Length (ft.)	8.5					
DIMENSIONAL DATA	DIMENSIONAL DATA					
Capacity (12oz.btls./12oz.cans)	12 Cases / 15 Cases ‡					
Net Capacity (cu. ft.)	8.5					
Ext. Length Overall (in.)	363/4 (933mm)					
Ext. Depth Overall (in.)*	261/2 (673mm)					
Ext. Height Overall (in.)†	331/4 (845mm)					
Net Weight (lbs.)	190					
Gross Weight (lbs.)	221					
# of Dividers	2					
# of Casters	5EA					

Design and specifications subject to change without notice. Actual shipping weight may differ due to extra packing materials for product protection.

* Depth does not include 2" for cap catcher or 2" for rear spacers.

† Height does not include 5" for caster height.

‡ Case capacity refers to 24 pack.

• WARRANTY : 3 Year Parts and Labor Warranty Additional 2 Year Warranty on Compressor


- Anti-corrosion coated evaporator
- Self-contained system
- 4" dia. swivel casters standard


OPTIONAL ACCESSORIES :

- □ 2" caster for underbar series, ½" diameter: P0165B0100 (non-brake), P0165B0110 (w/ brake
- 5" caster, ½" diameter & 13 TPI: M726500100 (non-brake), M726500200 (w/ brake)
- □ 6" adjustable stainless steel leg: P0121P0100

363/4 (933mm)

PLAN VIEW





Ver.20171025



- **Turbo Air** : 800-627-0032 **GK** : 800-500-3519
- Warranty : 800-381-7770 AC : 888-900-1002



(GERMAN) KNIFE

