

4184 E. Conant St. Long Beach, CA 90808 Tel. 310-900-1000 Fax. 310-900-1077 www.turboairinc.com

Project :		
Model #:		
Item #:	Qty:	
Available W/H:		
Approval :		

**Model: TBC-50SD/SB-GF-N** 

# Glass / Mug Frosters

Underbar Equipment Super Deluxe Series

#### Patented Self-Cleaning Condenser



This product is equipped with a fine mesh filter to the front of the condenser to catch dust, and a rotating brush that moves up and down daily to remove excess buildup outward and away.



TBC-50SD-GF-N



TBC-50SB-GF-N

### \_\_\_ FEATURES & BENEFITS =\_\_

#### Self-Cleaning Condenser

The accumulation of dust in the condenser can cause the failure or breakdown of refrigerators. Refrigerators run normally until they reach a certain level of accumulation. At some point, when they are over the limit, their performance drops quickly resulting in damage to, or disposal of the stored products inside. The Self-Cleaning Condenser device keeps the condenser clean and prevents system failure by automatically brushing

#### ■ Hydrocarbon refrigerants (R-290)

With innovative and eco-friendly technology. Turbo Air brings you hydrocarbon refrigerators designed to meet the new standards of the EPA and DOE in 2017. Hydrocarbon refrigerants do not deplete the ozone layer and have very low contribution to global warming (ODP-0, GWP-3).

#### Stainless steel cabinet construction

Super Deluxe (SD) models boast a stainless steel exterior (except galvanized steel back and bottom). SB models have an attractive wear-resistant black vinyl exterior. Heavy gauge stainless steel countertop and glide lids are perfect for sanitation and durability. The interior is stainless steel except galvanized steel top. Turbo Air Glass Froster model guarantees the utmost in cleanliness and long product life. It also adds a touch of style to the most refined setting.

#### High-density polyurethane insulation

The entire cabinet structure is foamed-in-place using high density, CFC free polyurethane insulation.

#### ■ Heavy duty, PE (polyethylene) coated dividers Heavy duty 10mm thick pure grade PE coated shelves are provided

- Manual defrost system
- Direct cooling type

for maximum storage use.

- Huge capacity cooler cabinet requires only minimum floor space
- Side mount compressor unit
- Glass/mug froster holds -5°F ~ 15°F for the best in chilling glasses and plates













Model	Sliding Door	CU./FT.	Capacity 8" Mug / 10oz Stein	# of Shelves	НР	AMPS	Crated Weight (lbs.)	L x D*x H† (inches)
TBC-50SD-GF-N	2 2	13.85	140 / 386 Cups	5	1/3	1.7	280	50 x 261/2 x 331/4
TBC-50SB-GF-N		13.85	140 / 386 Cups	5	1/3	1.7	280	50 x 261/2 x 331/4

(unit: inch)

# Glass / Mug Frosters

# **Model: TBC-50SD/SB-GF-N**

ELECTRICAL DATA					
Voltage	115/60/1				
Plug Type					
Full Load Amperes	1.7				
Compressor HP	1/3				
Refrigerant	R-290				
Cord Length (ft.)	8.5				
DIMENSIONAL DATA					
Capacity (8" Mug / 10oz Stein)	140 Cups / 386 Cups				
Net Capacity (cu. ft.)	13.85				
Ext. Length Overall (in.)	50 (1270mm)				
Ext. Depth Overall (in.)*	261/2 (673mm)				
Ext. Height Overall (in.)†	331/4 (845mm)				
Net Weight (lbs.)	240				
Gross Weight (lbs.)	280				
# of Shelves	5				
# of Casters	5EA				

Design and specifications subject to change without notice.

Actual shipping weight may differ due to extra packing materials for product protection.

- \* Depth does not include 2" for rear spacers.
- † Height does not include 5" for caster height.


## 3 Year Parts and Labor Warranty Additional 2 Year Warranty on Compressor **WARRANTY:**


- Anti-corrosion coated evaporator
- Self-contained system
- 4" dia. swivel casters standard
- 2" dia. casters available (optional)
- 6" height adjustable legs available (optional)


#### OPTIONAL ACCESSORIES :

- ☐ 2" caster for underbar series, ½" diameter: P0165B0100 (non-brake), P0165B0110 (w/ brake)
- ☐ 5" caster, ½" diameter & 13 TPI: M726500100 (non-brake), M726500200 (w/ brake)
- ☐ 6" adjustable stainless steel leg: P0121P0100

### **PLAN VIEW**







Ver.20171106











■ **Turbo Air**: 800-627-0032 ■ **GK**: 800-500-3519

■ Warranty: 800-381-7770 ■ AC: 888-900-1002









