

4184 E. Conant St. Long Beach, CA 90808 Tel. 310-900-1000 Fax. 310-900-1077 www.turboairinc.com

Project		
i i ujeci	•	

Model # : Item # :

Available W/H :

Approval :

Swing Door Freezers

____ FEATURES & BENEFITS ____

Self-Cleaning Condenser

The accumulation of dust in the condenser can cause the failure or breakdown of refrigerators. Refrigerators run normally until they reach a certain level of accumulation. At some point, when they are over the limit, their performance drops quickly resulting in damage to, or disposal of the stored products inside. The Self-Cleaning Condenser device keeps the condenser clean and prevents system failure by automatically brushing daily.

Digital temperature control & monitor system

- Keep food products safe by maintaining constant temperatures.
- Alarms that sound when doors are not sealed shut; protect against food spoilage that originate from cold air leaks.
- Early Warning Alarm program detect issues before malfunction occurs.
- Digital display allows for easy monitoring.
- Programs interpret the condition of refrigeration systems by self-diagnosis.
- Rapid cool-down function (Turbo freeze).
- Smart defrost system will defrost as needed.
- Automatic evaporator fan motor delays.

Hydrocarbon refrigerants (R-290)

With innovative and eco-friendly technology, Turbo Air brings you hydrocarbon refrigerators designed to meet the new standards of the EPA and DOE in 2017. Hydrocarbon refrigerants do not deplete the ozone layer and have very low contribution to global warming (ODP-0, GWP-3).

Energy conserving fan control

Utilizing algorithmic air circulation for optimal temperature levels, our innovative fan control system conserves energy by at least 15% and increases compressor life by up to 30%.

No electrical cabinet heater is needed

Turbo Air is the first in the industry to replace a frame heater with a method of using compressor-produced heat. This eliminates any unnecessary energy consumption while providing efficient freezing performance.

Shadow free advertising panel

Turbo Air is a pioneer in the refrigerator industry on applying special LED Light Guided Panels (LGP). LGP increases panel visibility and eliminates shadows, enhancing any store atmosphere with eye-catching effects. LED lighting offers 5 times longer lasting life than fluorescents and conserves energy as well.

High-density polyurethane insulation

The entire cabinet structure is foamed-in-place using high density, CFC free polyurethane insulation.

Triple pane heated glass doors

Equipped with unique triple-pane heated glass doors which enhance energy efficiency by preventing heat transfers and minimizing condensation. Lightweight door construction reduces door maintenance, bushing wear, and facilitates smooth door opening.

LED lighting interior



Qty :

Model : TGF-15SD-N



TGF-15SDW-N

Freezer holds -10°F ~ 5°F for the best in frozen food preservation





Model	Swing Door	CU./FT.	#of Shelves	HP	AMPS	Crated Weight (lbs.)	$L \ge D^* \ge H^+$ (inches)
TGF-15SD-N	1	13.2	4	1/2	5.6	313	263/8 x 243/4 x 755/8

Ver.20171127

*Depth does not include 2-1/4" (57mm) for door handle. † Height does not include 1-5/8" (42mm) for leg height.

Swing Door Freezers

Model : TGF-15SD-N

ELECTRICAL DATA				
Voltage	115/60/1			
Plug Type	() NEMA 5-15P			
Full Load Amperes	5.6			
Compressor HP	1/2			
Cord Length (ft.)	7			
Refrigerant	R-290			
DIMENSIONAL DATA				
# of Doors	1			
Net Capacity (cu. ft.)	13.2			
Ext. Length Overall (in.)	263/8 (670mm)			
Ext. Depth Overall (in.)*	24 _{3/4} (630mm)			
Ext. Height Overall (in.)†	755/8 (1920mm)			
Int. Length Overall (in.)	22 (560mm)			
Int. Depth Overall (in.)	201/4 (515mm)			
Int. Height Overall (in.)	613/8 (1560mm)			
# of Shelves	4			
Shelf Size (L x D) (in.)	201/2 x 161/2			
Net Weight (lbs.)	290			
Gross Weight (lbs.)	313			

Design and specifications subject to change without notice. Actual shipping weight may differ due to extra packing materials for product protection.

* Depth does not include 2-1/4" (57mm) for door handle.


† Height does not include 1-5/8" (42mm) for leg height.

• WARRANTY : ³ Year Parts and Labor Warranty Additional 2 Year Warranty on Compressor

- Anti-corrosion coated evaporator
- Adjustable PE (polyethylene) coated wire shelves
- Door locks standard
- Price tag channel available (optional)
- 2.5" dia. casters available -½" dia. & 13 TPI (optional)
- *Two color options available (standard):* white cabinet (W), black cabinet with black color trim (B).

OPTIONAL ACCESSORIES :

- 2.5" caster, ½" diameter & 13 TPI: 30265H0100 (non-brake), 30265H0200 (w/ brake)
- □ Additional PE coated wire shelf: P0178U0200
- Price tag channel: P0122K5100 (20-1/4"L)



Ver.20171127



- **Turbo Air** : 800-627-0032 **GK** : 800-500-3519
- Warranty : 800-381-7770 AC : 888-900-1002

SIDE VIEW

~

Turbo air

MAN (<u>KNIFE</u>) **IIR**

(GERMAN

