

REFRIGERATOR MANUFACTURER
Turbo air
 more durable, efficient, beautiful

4184 E. Conant St.
 Long Beach, CA 90808
 Tel. 310-900-1000
 Fax. 310-900-1077
www.turboairinc.com

| | |
|-------------------|--------|
| Project: | |
| Model #: | |
| Item #: | |
| Available W/H: | Qty: |
| Approval: | |
| ALA #: | SIS #: |
| CSI Section 11400 | |

Island Display Cases

Self-Serve Merchandisers

Patented Self-Cleaning Condenser



This product is equipped with a fine mesh filter to the front of the condenser to catch dust, and a rotating brush that moves up and down daily to remove excess buildup outward and away.

Model : TIOM-36RSB-N



FEATURES & BENEFITS

Self-Cleaning Condenser

The accumulation of dust in the condenser causes the failure or breakdown of refrigerators. Refrigerators run normally until they reach a certain level of accumulation. At some point, when they are over the limit, their performance drops quickly resulting in damage to, or disposal of the stored products in refrigerators. The Self-Cleaning Condenser device keeps the condenser clean and prevents system failure by automatically brushing daily.

Hydrocarbon refrigerant (R-290)

With innovative and eco-friendly technology, Turbo Air brings you hydrocarbon refrigerators designed to meet DOE's Energy Conservation Standards in 2017 and to use EPA's SNAP Program approved HC refrigerants. Hydrocarbon refrigerants do not deplete the ozone layer and have very low contribution to global warming (ODP-0, GWP-3).

Modern design

By harmonizing curvature and rigidity, our modern style product designs are user-friendly while maintaining the highest product visibility and aesthetics. The glass front shield optimizes the merchandiser's display effects of fresh salads, sandwiches, desserts and beverages.

Designed to enhance impulsive sales

Ideal for eye-catching displays and convenient access with fast service in high traffic area.

LED lighting on top panel and canopy

Brighter and longer lasting LED lights provide attractive, enhanced illumination compared to fluorescents. It saves energy by producing less heat, while maximizing the visibility in the display area.

ABS bump guard liners

5mm thick durable clear PC (polycarbonate) product stopper

Simple plug-in installation

Patented self-contained system, no plumbing required

Digital electronic thermostat with defrost control

Price tag rails standard

NATURAL
Refrigerant




| Model | CU./FT. | # of Tiers | HP | AMPS | Crated Weight (lbs.) | L x D x H* (inches) |
|---------------------|-----------|------------|----------------|--------------|----------------------|-------------------------|
| TIOM-36RSB-N | 20 | 3 | 3/4 x 4 | 16.43 | 1225 | 48 x 61 3/4 x 65 |

Island Display Cases

Self-Serve Merchandisers

Model : TIOM-36RSB-N

| ELECTRICAL DATA | |
|-----------------------------------|---|
| Voltage | 220/60/1 |
| Plug Type |  NEMA L6-20P |
| Full Load Amperes | 16.43 |
| Compressor HP | 3/4 x 4 |
| Cord Length (ft.) | 97/8 |
| Refrigerant | R-290 |
| DIMENSIONAL DATA | |
| Net Capacity (cu. ft.) | 20 |
| Ext. Dimension (L x D x H*) (in.) | 48 x 61 3/4 x 65 |
| # of Tiers | 3 |
| Net Weight (lbs.) | 816 |
| Gross Weight (lbs.) | 1225 |

Design and specifications subject to change without notice.

Actual shipping weight may differ due to extra packing materials for product protection.

* Height does not include 5/8" for bolt height.

■ **WARRANTY : 2 Year Parts and Labor Warranty**
Additional 3 Year Warranty on Compressor

■ STANDARD FEATURES

- Standard color comes in black only
- Bolt height adjustable up to 2 3/4"

■ Recommended operating conditions


TIOM models are designed to operate in an environment where temperature & humidity do not exceed 75°F and 55% respectively. Units should not be installed near HVAC vents, fans or doorways that will disrupt the air curtain and compromise the function of the cabinet. Air curtain models will run most efficiently when completely loaded with product.

■ OPTIONAL ACCESSORIES


- 1.6" caster: CAS16WBT00 (non-brake)
- 4" caster, 1/2" diameter & 13 TPI: G8F6500101 (non-brake), G8F6500201 (w/ brake)
- 6" leveling seismic leg (1/2", 13 TPI): 30221M0700

PLAN VIEW


(unit : inch)



TOP VIEW



FRONT VIEW



SIDE VIEW

Ver.20210701

NATURAL
Refrigerant



■ Turbo Air : 800-627-0032

■ GK : 800-500-3519

■ Warranty : 800-381-7770

■ AC : 888-900-1002

TURBO air REFRIGERATION MANUFACTURER

GERMAN KNIFE

RADIANCE

TURBO air REFRIGERATION SYSTEM

TEXAKING

Continued product development may necessitate specification changes without notice.