

4184 E. Conant St. Long Beach, CA 90808 Tel. 310-900-1000 Fax. 310-900-1077 www.turboairinc.com

Project :		
Model #:		
Item #:	Qty:	
Available W/H :		
Approval :		

Model: TWR-60SD-D4-N

Worktop Refrigerator - Drawers

Worktops Super Deluxe Series

Patented Self-Cleaning Condenser



This product is equipped with a fine mesh filter to the front of the condenser to catch dust, and a rotating brush that moves up and down daily to remove excess buildup outward and away.



___ FEATURES & BENEFITS =__

Self-Cleaning Condenser

The accumulation of dust in the condenser can cause the failure or breakdown of refrigerators. Refrigerators run normally until they reach a certain level of accumulation. At some point, when they are over the limit, their performance drops quickly resulting in damage to, or disposal of the stored products inside. The Self-Cleaning Condenser device keeps the condenser clean and prevents system failure by automatically brushing daily.

Digital temperature control & monitor system
 Keep food products safe by maintaining constant temperatures.

External digital display allows for easy monitoring.

■ Hydrocarbon refrigerants (R-290)

With innovative and eco-friendly technology, Turbo Air brings you hydrocarbon refrigerators designed to meet the new standards of the EPA and DOE in 2017. Hydrocarbon refrigerants do not deplete the ozone layer and have very low contribution to global warming (ODP-0, GWP-3).

Stainless steel cabinet construction

The Turbo Air Super Deluxe model boasts a stainless steel interior and exterior (galvanized steel back & bottom). It guarantees the utmost in cleanliness and long product life. The Super Deluxe adds a touch of style to the most refined setting.

Sturdy, clean stainless steel shelving

Shelves are the most important part of cleanliness as they come in direct contact with food. After a while, PVC coated wire shelves may peel, rust and lead to unsanitary conditions. Only the Turbo Air Super Deluxe series uniquely provides stainless steel shelving.

■ Ergonomically designed doors

Customers' fatigue fades away with easy grip handles and doors that open effortlessly. These features along with self-closing doors make this the ultimate choice in customer convenience. ABS sheet door liners resist water condensation with thermal efficiency.

■ High-density polyurethane insulation

The entire cabinet structure and solid doors are foamed-in-place using high density, CFC free polyurethane insulation.

Magnetic door gaskets

Magnetic door gaskets are of one-piece construction, removable without tools for ease of cleaning and replacement.

■ Refrigerator holds 33°F ~ 38°F for the best in food preservation











	Swing			#of			Crated	$L \times D^* \times H^{\dagger}$
Model	Door	Drawers	CU./FT.	Shelves	HP	AMPS	Weight (lbs.)	(inches)
TWR-60SD-D4-N	-	4	16	-	1/6	2.4	312	601/4 x 30 x 331/2

Model: TWR-60SD-D4-N

ELECTRICAL DATA						
Voltage	115/60/1					
Plug Type	① NEMA 5-15P					
Full Load Amperes	2.4					
Compressor HP	1/6					
Cord Length (ft.)	9					
Refrigerant	R-290					
DIMENSIONAL DATA						
Net Capacity (cu. ft.)	16					
Ext. Length Overall (in.)	601/4 (1530mm)					
Ext. Depth Overall (in.)*	30 (762mm)					
Ext. Height Overall (in.)†	331/2 (851mm)					
# of Doors	-					
# of Shelves	-					
Net Weight (lbs.)	272					
Gross Weight (lbs.)	312					

Design and specifications subject to change without notice.

Actual shipping weight may differ due to extra packing materials for product protection.


■ WARRANTY: 3 Year Parts and Labor Warranty **Additional 2 Year Warranty on Compressor**

- Anti-corrosion coated evaporator
- Self-contained system
- Standard 4" dia. swivel casters with locks on the front set
- Backsplash standard
- 2.5" caster available (optional)
- Legs available (optional)


■ OPTIONAL ACCESSORIES:

- ☐ 2.5" caster, ½" diameter & 13 TPI: 30265H0100 (non-brake), 30265H0200 (w/ brake)
- ☐ 5" caster, ½" diameter & 13 TPI: M726500100 (non-brake), M726500200 (w/ brake)
- ☐ 6" ABS plastic leg: 30221M0200
- ☐ 6" stainless steel leg: 30221M0600

PLAN VIEW (unit: inch)



PLAN VIEW



SIDE VIEW

Ver 20180112














■ Warranty: 800-381-7770 ■ AC: 888-900-1002











^{*} Depth does not include 1" for rear spacers. † Height does not include 5" for caster height.