

4184 E. Conant St. Long Beach, CA 90808 Tel. 310-900-1000 Fax. 310-900-1077 www.turboairinc.com

Project :		
Model #:		
Item #:	Qty:	
Available W/H :		
Approval:		

**Model: TBC-50SD/SB-N6** 

# **Bottle Coolers**

Underbar Equipment Super Deluxe Series

#### Patented Self-Cleaning Condenser



This product is equipped with a fine mesh filter to the front of the condenser to catch dust, and a rotating brush that moves up and down daily to remove excess buildup outward and away.







TBC-50SB-N6

## = FEATURES & BENEFITS=

### Self-Cleaning Condenser

The accumulation of dust in the condenser can cause the failure or breakdown of refrigerators. Refrigerators run normally until they reach a certain level of accumulation. At some point, when they are over the limit, their performance drops quickly resulting in damage to, or disposal of the stored products inside. The Self-Cleaning Condenser device keeps the condenser clean and prevents system failure by automatically brushing daily.

#### ■ Hydrocarbon refrigerants (R-600a)

With innovative and eco-friendly technology, Turbo Air brings you hydrocarbon refrigerators designed to meet the new standards of the EPA and DOE in 2017. Hydrocarbon refrigerants do not deplete the ozone layer and have very low contribution to global warming (ODP-0, GWP-3).

#### ■ Forced air cooling system

Positive guided forced air cooling system chills bottles on top first.

#### Stainless steel cabinet construction

Super Deluxe (SD) models boast a stainless steel exterior (except galvanized steel back and bottom). SB models are attractive wear-resistant black vinyl exterior. Heavy gauge stainless steel countertop and glide lids are perfect for sanitation and durability. Interior is stainless steel except galvanized steel top. Turbo Air Bottle Cooler model guarantees utmost in cleanliness and long product life. It also can add a touch of style to the most refined setting.

■ High-density polyurethane insulation

The entire cabinet structure is foamed-in-place using high density, CFC free polyurethane insulation.

- Adjustable, heavy duty, PE (polyethylene) coated dividers
- Rugged built-in removable bottle cap opener and cap catcher
- Huge capacity cooler cabinet requires only minimum floor space

### Side mount compressor unit

With compressors positioned on the side of the unit, our refrigerators can now be serviced without being moved. Our innovative, front breathing feature also allows this model to be highly efficient in narrow spaces.

■ Refrigerator holds 33°F ~ 38°F for the best in beverage preservation













Model	Sliding Door	CU./FT.	Capacity 12oz.btls. / 12oz.cans	# of Dividers	НР	AMPS	Crated Weight (lbs.)	L x D*x H† (inches)
TBC-50SD-N6 TBC-50SB-N6		13.5 13.5	18 / 22.8 Cases 18 / 22.8 Cases	3 3	1/5 1/5	1.7 1.7	266 275	50 x 261/2 x 331/4 50 x 261/2 x 331/4

(unit: inch)

# **Bottle Coolers**

# Model: TBC-50SD/SB-N6

ELECTRICAL DATA					
Voltage	115/60/1				
Plug Type	① NEMA 5-15P				
Full Load Amperes	1.7				
Compressor HP	1/5				
Refrigerant	R-600a				
Cord Length (ft.)	9.8				
DIMENSIONAL DATA					
Capacity (12oz.btls./12oz.cans)	18 Cases / 22.8 Cases				
Net Capacity (cu. ft.)	13.5				
Ext. Length Overall (in.)	50 (1270mm)				
Ext. Depth Overall (in.)*	26 <sub>1/2</sub> (673mm)				
Ext. Height Overall (in.)†	331/4 (845mm)				
Net Weight (lbs.)	235				
Gross Weight (lbs.)	266/275				
# of Dividers	3				
# of Casters	5EA				

Design and specifications subject to change without notice.

Actual shipping weight may differ due to extra packing materials for product protection.

\* Depth does not include 2" for cap catcher or 2" for rear spacers.

† Height does not include 5" for caster height.


# ■ WARRANTY: 3 Year Parts and Labor Warranty Additional 2 Year Warranty on Compressor

- Anti-Corrosion Coated Evaporator
- Self-contained system
- 4" dia. swivel casters standard
- 2" dia. casters available (optional)
- 6" height adjustable legs available (optional)


#### ■ OPTIONAL ACCESSORIES:

- ☐ 2" caster for underbar series, ½" diameter: P0165B0100 (non-brake), P0165B0110 (w/ brak
- ☐ 5" caster, ½" diameter & 13 TPI: M726500100 (non-brake), M726500200 (w/ brake)
- ☐ 6" adjustable stainless steel leg: P0121P0100


## **PLAN VIEW**



**PLAN VIEW** 



**FRONT VIEW** 



SIDE VIEW

Ver.20170928











■ **Turbo Air**: 800-627-0032 ■ **GK**: 800-500-3519

■ Warranty: 800-381-7770 ■ AC: 888-900-1002









