

Long Beach, CA 90808 Tel. 310-900-1000 Fax. 310-900-1077 www.turboairinc.com

Project:		
Model #:		
Item #:		
Available W/H:		Qty:
Approval:		
AIA#:	SIS #:	
CSI Section 11400		

Sandwich / Salad Unit - Clear Lid

Food Prep Tables M3 Series

Model: MST-24S-N6



= FEATURES & BENEFITS =

- Digital temperature control & monitor system Keep food products safe by maintaining constant temperatures. External digital display allows for easy monitoring.
- Hydrocarbon refrigerants (R-600a) With innovative and eco-friendly technology, Turbo Air brings you hydrocarbon refrigerators designed to meet DOE's Energy Conservation Standards in 2017 and to use EPA's SNAP Program approved HC refrigerants. Hydrocarbon refrigerants do not deplete the ozone layer and have very low contribution to global warming (ODP-0, GWP-3).
- Cold Bunker system

Our innovative forced air system allows cold air to flow all around the food pan area, covering not only underneath the pan, but also the front, top and the rear. This unique air flow creates a cold air-shield around the pan, which maintains the food temperature at under 41°F (NSF requirement) even when the lids are opened. In addition, the compartment isolates pans from the reach-in area to prevent food spillage.

■ Front Breathing airflow

Front Breathing airflow is designed to draw in air and discharge from the front, allowing units to run at high efficiency in tight spaces and eliminates the need for surrounding clearances.

Stainless steel exterior

The Turbo Air M3 model boasts a stainless steel exterior (galvanized steel back and bottom). Interior is AL interior with stainless steel floor and ABS door liner. It guarantees the utmost in cleanliness and long product life. The M3 model adds a touch of style to the most refined setting.

High-density polyurethane insulation

The entire cabinet structure and solid doors are foamed-in-place using high density, CFC free polyurethane insulation.

- 9-1/2" deep, 1/2" thick high-density Polyethylene cutting board included with convenient side rail
- Adjustable, heavy duty, PE (polyethylene) coated wire shelves
- LED interior lighting & fan control

Energy efficient LED lighting lights every corner, making items easy to find. Fan control function automatically shuts off the fan when the door is open, which prevents hot air from being drawn in, thus maintaining the cool inner temperature

Refrigerator holds 33°F ~ 39°F for the best in food preservation













Swing #of #of Crated $L \times D^* \times H^{\dagger}$ Model CU./FT. Shelves HP **AMPS** Weight (lbs.) Doors Pans (inches) **MST-24S-N6** 1 2.83 1 1/5 2.6 137 24 x 235/8 x 281/8 6

Sandwich / Salad Unit - Clear Lid

Model: MST-24S-N6

ELECTRICAL DATA		
Voltage	115/60/1	
Plug Type	NEMA 5-15P	
Full Load Amperes	2.6	
Compressor HP	1/5	
Cord Length (ft.)	10	
Refrigerant	R-600a	
DIMENSIONAL DATA		
Ext. Length Overall (in.)	24 (610mm)	
Ext. Depth Overall (in.)*	23 _{5/8} (600mm)	
Ext. Height Overall (in.)†	281/8 (715mm)	
# of Doors	1	
# of Shelves	1	
# of Pans	6	
Net Capacity (cu. ft.)	2.83	
Shelf Size (L x D) (in.)	193/8 x 111/8	
Net Weight (lbs.)	126	
Gross Weight (lbs.)	137	

Design and specifications subject to change without notice.

Actual shipping weight may differ due to extra packing materials for product protection.

 * Depth does not include 1" for rear spacers. Depth does not include 3-3/8" for cutting board.

† Height does not include 3-7/8" for caster height.

■ WARRANTY: 3 Year Parts and Labor Warranty Additional 2 Year Warranty on Compressor


STANDARD FEATURES


- · Anti-corrosion coated evaporator
- · Self-contained system
- Standard 3" dia. swivel casters with locks on the front set
- Standard 1/6 size, 4" deep condiment pans included
- ** Lead time applies. Please contact your sales representative for more details to order.

OPTIONAL ACCESSORIES

- 2.5" caster, ½" diameter & 13 TPI: 30265H0100 (non-brake), 30265H0200 (w/ brake)
- 5" caster, ½" diameter & 13 TPI: M726500100 (non-brake), M726500200 (w/ brake)
- 6" stainless steel leg: 30221M0600
- Door lock: lead time applies. Please contact your sales representative for more details to order.

PLAN VIEW (unit: inch)





Ver.20210208

NATURAL Refrigerant









02.0200

■ **Turbo Air**: 800-627-0032 ■ **GK**: 800-500-3519

■ Warranty: 800-381-7770 ■ AC: 888-900-1002









