

Long Beach, CA 90808 Tel. 310-900-1000 Fax. 310-900-1077 www.turboairinc.com

Project:		
Model #:		
Item #:		
Available W/H:		Qty:
Approval:		
AIA#:	SIS #:	
CSI Section 11400		

Worktop Refrigerator - Shallow Depth

Worktops M3 Series

Model: MWR-27S-N6



____ FEATURES & BENEFITS ____

Digital temperature control & monitor system Keep food products safe by maintaining constant temperatures. External digital display allows for easy monitoring.

 Hydrocarbon refrigerants (R-600a)
With innovative and eco-friendly technology, Turbo Air brings you hydrocarbon refrigerators designed to meet DOE's Energy Conservation Standards in 2017 and to use EPA's SNAP Program approved HC refrigerants. Hydrocarbon refrigerants do not deplete the ozone layer and have very low contribution to global warming (ODP-0, GWP-3).

Stainless steel exterior

The Turbo Air M3 model boasts a stainless steel exterior (galvanized steel back and bottom). Interior is stainless steel floor with AL sides and back. It guarantees the utmost in cleanliness and long product life. The M3 model adds a touch of style to the most refined setting.

High-density polyurethane insulation

The entire cabinet structure and solid doors are foamed-in-place using high density, CFC free polyurethane insulation.

Ergonomically designed doors

Customers' fatigue fades away with easy grip handles and doors that open effortlessly. These features along with self-closing doors make this the ultimate choice in customer convenience. ABS sheet door liners resist water condensation with thermal efficiency.

LED interior lighting & fan control

Energy efficient LED lighting lights every corner, making items easy to find. Fan control function automatically shuts off the fan when the door is open, which prevents hot air from being drawn in, thus maintaining the cool inner temperature.

- Adjustable, heavy duty, PE (polyethylene) coated wire shelves
- Refrigerator holds 33°F ~ 38°F for the best in food preservation

Model	Swing Doors	CU./FT.	#of Shelves	HP	AMPS	Crated Weight (lbs.)	$L x D^* x H^{\dagger}$ (inches)
MWR-27S-N6	1	3.28	1	1/6	2.4	147	27 x 221/2 x 291/8

Ver 20210121 Printed in U.S.A.

*Depth does not include 1" for rear spacers. † Height does not include 5" for caster height.

Worktop Refrigerator - Shallow Depth

Worktops M3 Series

Model: MWR-27S-N6

ELECTRICAL DATA				
Voltage	115/60/1			
Plug Type	(i) NEMA 5-15P			
Full Load Amperes	2.4			
Compressor HP	1/6			
Cord Length (ft.)	10			
Refrigerant	R-600a			
DIMENSIONAL DATA				
Net Capacity (cu. ft.)	3.28			
Ext. Length Overall (in.)	27 (686mm)			
Ext. Depth Overall (in.)*	221/2 (570mm)			
Ext. Height Overall (in.) [†]	291/8 (741mm)			
# of Doors	1			
# of Shelves	1			
Shelf Size (L x D) (in.)	223/8 x 111/8			
Net Weight (lbs.)	135			
Gross Weight (lbs.)	147			

Design and specifications subject to change without notice. Actual shipping weight may differ due to extra packing materials for product protection.

* Depth does not include 1" for rear spacers.

+ Height does not include 5" for caster height.

• WARRANTY : ³ Year Parts and Labor Warranty Additional 2 Year Warranty on Compressor


STANDARD FEATURES


- · Anti-corrosion coated evaporator
- Self-contained system
- Standard 4" dia. swivel casters with locks on the front set
- ** Lead time applies. Please contact your sales representative for more details to order.

OPTIONAL ACCESSORIES

- 1" caster, 1/2" diameter & 13 TPI: S28R813660 (non-brake)
- 2.5" caster, 1/2" diameter & 13 TPI: 30265H0100 (non-brake), 30265H0200 (w/ brake)
- 5" caster, 1/2" diameter & 13 TPI: M726500100 (non-brake), M726500200 (w/ brake)
- Leveling leg, 1/2" 13 TPI x 1.54": LFM1213566
- 6" ABS plastic leg: 30221M0200
- 6" stainless steel leg: 30221M0600
- · Door lock: Lead time applies. Please contact your sales representative for more details to order.

5 YEAR WARRANTY





SIDE VIEW

Ver.20210121



Turbo Air : 800-627-0032 **GK** : 800-500-3519

■ Warranty : 800-381-7770 ■ AC : 888-900-1002



Texaking Turbo air

Continued product development may necessitate specification changes without notice.