

BAKERY DISPLAY CASES NATURAL Refrigerant

Self-Cleaning Condenser Equipped Units

■ Self-Cleaning Condenser (Patented)

The accumulation of dust in the condenser can cause the failure or breakdown of refrigerators. Refrigerators run normally until they reach a certain level of accumulation. At some point, when they are over the limit, their performance drops quickly resulting in damage to, or disposal of the stored products inside. The Self-Cleaning Condenser device keeps the condenser clean and prevents system failure by automatically brushing daily.

■ Hydrocarbon refrigerants (R-290)

With innovative and eco-friendly technology, Turbo Air brings you hydrocarbon refrigerators designed to meet DOE's Energy Conservation Standards in 2017 and to use EPA's SNAP Program approved HC refrigerants. Hydrocarbon refrigerants do not deplete the ozone layer and have very low contribution to global warming (ODP-0, GWP-3).

■ Attractive, elegant, glass sided Euro design

Straight, tempered front & side glass with minimal frame provide full product visibility to optimize display effects. Its elegant contemporary euro design and luxurious colored case will not only enhance any store atmosphere but also will keep product presentation at its best and most beautiful.

■ High-density polyurethane insulation

The entire cabinet structure is foamed-in-place using high density, CFC free polyurethane insulation.

■ Digital temperature controller

■ Double pane glass is tempered for safety (Front heated glass)

■ Adjustable, tempered glass shelves with stainless steel front and back edges

■ Stainless steel floor and airflow grille

■ Sliding rear doors for product loading & unloading



Maintenance free,
Self-Cleaning Condenser

TBP36-46NN

TBP36-54NN

■ Rear access to compressor compartment for quick and easy service

■ Stainless steel color option available

■ Standard features

- No plumbing required
- Safety shielded LED interior lighting
- Standard color comes in black only
- 3" dia. swivel casters with locks on the rear set

■ Optional features

- White color option available (Lead time applies)

■ Recommended operating conditions

TBP models are designed to operate in an environment where temperature & humidity do not exceed 75°F and 55% respectively.

TBP-NN MODELS SPECIFICATIONS

ELECTRICAL DATA	TBP36-46NN	TBP48-46NN	TBP60-46NN
Voltage	115/60/1	115/60/1	115/60/1
Plug Type	Ⓜ NEMA 5-15P	Ⓜ NEMA 5-15P	Ⓜ NEMA 5-15P
Full Load Amperes	6	6.3	6.5
Compressor HP	1/3	1/3	3/4
Refrigerant	R-290	R-290	R-290
Net Capacity (cu. ft.)	9	12.4	15.7
Ext. Dimension (L x D x H) (in.)	35 ³ / ₈ x 27 ¹ / ₂ x 44 ³ / ₈ [†]	47 ¹ / ₄ x 27 ¹ / ₂ x 44 ³ / ₈ [†]	59 x 27 ¹ / ₂ x 44 ³ / ₈ [†]
# of Shelves	1	1	1
Shelf Size (in.)	29 ¹ / ₂ x 14 ¹ / ₂	41 ¹ / ₂ x 14 ¹ / ₂	53 x 14 ¹ / ₂
Net / Gross Weight (lbs.)	317 / 493	383 / 581	445 / 665

ELECTRICAL DATA	TBP36-54NN	TBP48-54NN	TBP60-54NN
Voltage	115/60/1	115/60/1	115/60/1
Plug Type	Ⓜ NEMA 5-15P	Ⓜ NEMA 5-15P	Ⓜ NEMA 5-15P
Full Load Amperes	6.0	6.5	6.8
Compressor HP	1/3	3/4	3/4
Refrigerant	R-290	R-290	R-290
Net Capacity (cu. ft.)	12.5	17.2	21.8
Ext. Dimension (L x D x H) (in.)	35 ³ / ₈ x 27 ¹ / ₂ x 52 ³ / ₈ [†]	47 ¹ / ₄ x 27 ¹ / ₂ x 52 ³ / ₈ [†]	59 x 27 ¹ / ₂ x 52 ³ / ₈ [†]
# of Shelves	2	2	2
Shelf Size (in.)	29 ¹ / ₂ x 12 ¹ / ₂ , 29 ¹ / ₂ x 14 ¹ / ₂	41 ¹ / ₂ x 12 ¹ / ₂ , 41 ¹ / ₂ x 14 ¹ / ₂	53 x 12 ¹ / ₂ , 53 x 14 ¹ / ₂
Net / Gross Weight (lbs.)	362 / 549	433 / 642	505 / 741

Design and specifications subject to change without notice. Most updated spec sheets are available at www.turboairinc.com.

Actual shipping weight may differ due to extra packing materials for product protection.

[†] Height does not include 2" for caster height.

■ WARRANTY: 2 Year Parts and Labor Warranty, Additional 3 Year Warranty on Compressor

BAKERY DISPLAY CASES NATURAL Refrigerant

Self-Cleaning Condenser Equipped Units

■ Self-Cleaning Condenser (Patented)

The accumulation of dust in the condenser can cause the failure or breakdown of refrigerators. Refrigerators run normally until they reach a certain level of accumulation. At some point, when they are over the limit, their performance drops quickly resulting in damage to, or disposal of the stored products inside. The Self-Cleaning Condenser device keeps the condenser clean and prevents system failure by automatically brushing daily.

■ Hydrocarbon refrigerants (R-290)

With innovative and eco-friendly technology, Turbo Air brings you hydrocarbon refrigerators designed to meet DOE's Energy Conservation Standards in 2017 and to use EPA's SNAP Program approved HC refrigerants. Hydrocarbon refrigerants do not deplete the ozone layer and have very low contribution to global warming (ODP-0, GWP-3).

■ Attractive, elegant, glass sided Euro design

Straight, tempered front & side glass with minimal frame provide full product visibility to optimize display effects. Its elegant contemporary euro design and luxurious colored case will not only enhance any store atmosphere but also will keep product presentation at its best and most beautiful.

■ High-density polyurethane insulation

The entire cabinet structure is foamed-in-place using high density, CFC free polyurethane insulation.

■ Digital temperature controller

■ Double pane glass is tempered for safety (Front heated glass)

■ Adjustable, tempered glass shelves with stainless steel front and back edges

■ Stainless steel floor and airflow grille

■ Rear access to compressor compartment for quick and easy service

■ Stainless steel color option available



Sliding rear doors and front glass opening

Sliding rear doors make it easily accessible and convenient to arrange products. These doors are built to withstand constant sliding open and close. The front glass opens just enough to clean the interior effortlessly.

■ Standard features

- No plumbing required
- Safety shielded LED interior lighting
- Standard color comes in black only
- 3" dia. swivel casters with locks on the rear set

■ Optional features

- White color option available (Lead time applies)

- Recommended operating conditions

TBP models are designed to operate in an environment where temperature & humidity do not exceed 75°F and 55% respectively.

TBP-FN MODELS SPECIFICATIONS

ELECTRICAL DATA	TBP36-46FN	TBP48-46FN	TBP60-46FN
Voltage	115/60/1	115/60/1	115/60/1
Plug Type	① NEMA 5-15P	① NEMA 5-15P	① NEMA 5-15P
Full Load Amperes	6.3	6.8	7.3
Compressor HP	1/3	1/3	3/4
Refrigerant	R-290	R-290	R-290
Net Capacity (cu. ft.)	9	12.4	15.7
Ext. Dimension (L x D x H) (in.)	35 3/8 x 27 1/2 x 44 3/8†	47 1/4 x 27 1/2 x 44 3/8†	59 x 27 1/2 x 44 3/8†
# of Shelves	1	1	1
Shelf Size (in.)	29 1/2 x 14 1/2	41 1/2 x 14 1/2	53 x 14 1/2
Net / Gross Weight (lbs.)	327 / 503	398 / 596	465 / 685

ELECTRICAL DATA	TBP36-54FN	TBP48-54FN	TBP60-54FN
Voltage	115/60/1	115/60/1	115/60/1
Plug Type	① NEMA 5-15P	① NEMA 5-15P	① NEMA 5-15P
Full Load Amperes	7.0	8.2	8.7
Compressor HP	1/3	3/4	3/4
Refrigerant	R-290	R-290	R-290
Net Capacity (cu. ft.)	12.5	17.2	21.8
Ext. Dimension (L x D x H) (in.)	35 3/8 x 27 1/2 x 52 3/8†	47 1/4 x 27 1/2 x 52 3/8†	59 x 27 1/2 x 52 3/8†
# of Shelves	2	2	2
Shelf Size (in.)	29 1/2 x 12 1/2, 29 1/2 x 14 1/2	41 1/2 x 12 1/2, 41 1/2 x 14 1/2	53 x 12 1/2, 53 x 14 1/2
Net / Gross Weight (lbs.)	362 / 549	433 / 642	505 / 741

Design and specifications subject to change without notice. Most updated spec sheets are available at www.turboairinc.com.

Actual shipping weight may differ due to extra packing materials for product protection.

† Height does not include 2" for caster height.

■ WARRANTY: 2 Year Parts and Labor Warranty, Additional 3 Year Warranty on Compressor

DROP IN TYPE BAKERY DISPLAY CASES NATURAL Refrigerant

Self-Cleaning Condenser Equipped Units

■ Self-Cleaning Condenser (Patented)

The accumulation of dust in the condenser can cause the failure or breakdown of refrigerators. Refrigerators run normally until they reach a certain level of accumulation. At some point, when they are over the limit, their performance drops quickly resulting in damage to, or disposal of the stored products inside. The Self-Cleaning Condenser device keeps the condenser clean and prevents system failure by automatically brushing daily.

■ Hydrocarbon refrigerants (R-290)

With innovative and eco-friendly technology, Turbo Air brings you hydrocarbon refrigerators designed to meet DOE's Energy Conservation Standards in 2017 and to use EPA's SNAP Program approved HC refrigerants. Hydrocarbon refrigerants do not deplete the ozone layer and have very low contribution to global warming (ODP-0, GWP-3).

■ Attractive, elegant, glass sided Euro design

Straight, tempered front & side glass with minimal frame provide full product visibility to optimize display effects. Its elegant contemporary euro design and luxurious colored case will not only enhance any store atmosphere but also will keep product presentation at its best and most beautiful.

■ High-density polyurethane insulation

The entire cabinet structure is foamed-in-place using high density, CFC free polyurethane insulation.

■ Digital temperature controller

■ Double pane glass is tempered for safety (Front heated glass)

■ Adjustable, tempered glass shelves with stainless steel front and back edges

■ Stainless steel floor and airflow grille

■ Sliding rear doors and front glass for product loading & unloading



Maintenance free,
Self-Cleaning Condenser

* Bottom portion will not be visible after installation

TBP36-46FDN



TBP48-46FDN

■ Rear access to compressor compartment for quick and easy service

■ Standard features

- No plumbing required
- Safety shielded LED interior lighting
- 3" dia. swivel casters with locks on the rear set

- Recommended operating conditions

TBP models are designed to operate in an environment where temperature & humidity do not exceed 75°F and 55% respectively.

TBP-FDN MODELS SPECIFICATIONS

ELECTRICAL DATA	TBP36-46FDN	TBP48-46FDN	TBP60-46FDN
Voltage	115/60/1	115/60/1	115/60/1
Plug Type	① NEMA 5-15P	① NEMA 5-15P	① NEMA 5-15P
Full Load Amperes	6.3	6.8	7.3
Compressor HP	1/3	1/3	3/4
Refrigerant	R-290	R-290	R-290
Net Capacity (cu. ft.)	9	12.4	15.7
Ext. Dimension (L x D x H) (in.)	35 3/8 x 27 1/2 x 44 3/8†	47 1/4 x 27 1/2 x 44 3/8†	59 x 27 1/2 x 44 3/8
# of Shelves	1	1	1
Shelf Size (in.)	29 1/2 x 14 1/2	41 1/2 x 14 1/2	53 x 14 1/2
Net / Gross Weight (lbs.)	327 / 503	398 / 596	465 / 685

ELECTRICAL DATA	TBP36-54FDN	TBP48-54FDN	TBP60-54FDN
Voltage	115/60/1	115/60/1	115/60/1
Plug Type	① NEMA 5-15P	① NEMA 5-15P	① NEMA 5-15P
Full Load Amperes	7	8.2	8.7
Compressor HP	1/3	3/4	3/4
Refrigerant	R-290	R-290	R-290
Net Capacity (cu. ft.)	12.6	17.2	21.8
Ext. Dimension (L x D x H) (in.)	35 3/8 x 27 1/2 x 52 3/8†	47 1/4 x 27 1/2 x 52 3/8†	59 x 27 1/2 x 52 3/8†
# of Shelves	2	2	2
Shelf Size (in.)	29 1/2 x 12 1/2, 29 1/2 x 14 1/2	41 1/2 x 12 1/2, 41 1/2 x 14 1/2	53 x 12 1/2, 53 x 14 1/2
Net / Gross Weight (lbs.)	362 / 549	433 / 642	505 / 741

Design and specifications subject to change without notice. Most updated spec sheets are available at www.turboairinc.com.

Actual shipping weight may differ due to extra packing materials for product protection.

† Height does not include 2" for caster height.

■ WARRANTY: 2 Year Parts and Labor Warranty, Additional 3 Year Warranty on Compressor