

Long Beach, CA 90808 Tel. 310-900-1000 Fax. 310-900-1077 www.turboairinc.com

Project:		
Model #:		
Item #:		
Available W/H:		Qty:
Approval:		
AIA#:	SIS #:	
CSI Section 11400		

Swing Door Freezers

____ FEATURES & BENEFITS ____

Self-Cleaning Condenser

The accumulation of dust in the condenser can cause the failure or breakdown of refrigerators. Refrigerators run normally until they reach a certain level of accumulation. At some point, when they are over the limit, their performance drops quickly resulting in damage to, or disposal of the stored products inside. The Self-Cleaning Condenser device keeps the condenser clean and prevents system failure by automatically brushing daily.

Digital temperature control & monitor system

- Keep food products safe by maintaining constant temperatures. • Alarms that sound when doors are not sealed shut; protect against food spoilage that originate from cold air leaks.
- · Early Warning Alarm program detect issues before malfunction occurs.
- · Digital display allows for easy monitoring.
- · Programs interpret the condition of refrigeration systems by self-diagnosis.
- Rapid cool-down function (Turbo freeze).
- · Smart defrost system will defrost as needed.
- · Automatic evaporator fan motor delays.

Hydrocarbon refrigerants (R-290)

With innovative and eco-friendly technology, Turbo Air brings you hydrocarbon refrigerators designed to meet DOE's Energy Conservation Standards in 2017 and to use EPA's SNAP Program approved HC refrigerants. Hydrocarbon refrigerants do not deplete the ozone layer and have very low contribution to global warming (ODP-0, GWP-3).

Energy conserving fan control

Utilizing algorithmic air circulation for optimal temperature levels, our innovative fan control system conserves energy by at least 15% and increases compressor life by up to 30%.

No electrical cabinet heater is needed

Turbo Air is the first in the industry to replace a frame heater with a method of using compressor-produced heat. This eliminates any unnecessary energy consumption while providing efficient freezing performance.

Shadow free advertising panel

Turbo Air is a pioneer in the refrigerator industry on applying special LED Light Guided Panels (LGP). LGP increases panel visibility and eliminates shadows, enhancing any store atmosphere with eye-catching effects. LED lighting offers 5 times longer lasting life than fluorescents and conserves energy as well.

High-density polyurethane insulation

Swing

Door

1

The entire cabinet structure is foamed-in-place using high density, HCFC free polyurethane insulation.

Triple pane heated glass doors

Equipped with unique triple-pane heated glass doors which enhance energy efficiency by preventing heat transfers and minimizing condensation. Lightweight door construction reduces door maintenance, bushing wear, and facilitates smooth door opening.

CU./FT.

17.99

#of

Shelves

4





Model : TGF-23SD*-N



TGF-23SDW-N6



Freezer holds -10°F ~ 5°F for the best in frozen food preservation

	NATURAL Refrigerant	Intertek	US STEAR THE AND A COMPARENT A
HP	AMPS	Crated Weight (lbs.)	$L \ge D^* \ge H^\dagger$ (inches)
2/3	6.0	365	27 x 301/4 x 77

TGF-23SD*-N Ver 20210430 Printed in U.S.A.

Model

*Depth does not include 2-1/4" (57mm) for door handle. + Height does not include 2-1/2" (63mm) for leg height. *White cabinet(W), Black cabinet(B).

Swing Door Freezers

Model : TGF-23SD*-N

ELECTRICAL DATA		
Voltage	115/60/1	
Plug Type	(i) NEMA 5-15P	
Full Load Amperes	6.0	
Compressor HP	2/3	
Cord Length (ft.)	7	
Refrigerant	R-290	
DIMENSIONAL DATA		
# of Doors	1	
Net Capacity (cu. ft.)	17.99	
Ext. Length Overall (in.)	27 (685mm)	
Ext. Depth Overall (in.)*	301/4 (770mm)	
Ext. Height Overall (in.)†	77 (1955mm)	
Int. Length Overall (in.)	23 (585mm)	
Int. Depth Overall (in.)	253/4 (655mm)	
Int. Height Overall (in.)	603/8 (1535mm)	
# of Shelves	4	
Shelf Size (L x D) (in.)	21 1/2 x 22 1/2	
Net Weight (lbs.)	343	
Gross Weight (lbs.)	365	

Design and specifications subject to change without notice.

Actual shipping weight may differ due to extra packing materials for product protection. * Depth does not include 2-1/4" (57mm) for door handle.

+ Height does not include 2-1/2" (63mm) for leg height.

3 Year Parts and Labor Warranty WARRANTY: Additional 4 Year Warranty on Compressor

STANDARD FEATURES

- Anti-corrosion coated evaporator
- Door locks standard
- * Two color options available (standard): Super Deluxe series comes in white cabinet (W), black cabinet with black color trim (B).

OPTIONAL ACCESSORIES

- 4" caster, 1/2" diameter & 13 TPI: G8F6500101 (non-brake), G8F6500201 (w/ brake)
- Additional PE coated wire shelf: 30278R0102
- Price tag channel: P0122K5100 (20-1/4"L)
- Sign panel (blank): P0145A1800

SPEC

Turbo air

NATURAL


Refrigerant

Intertek

Intertel

3 YEAR

7 YEAR WARRANTY



Ver.20210430

ENERGY STAR®

Qualified

- **Turbo Air** : 800-627-0032 **GK** : 800-500-3519
- Warranty : 800-381-7770 AC : 888-900-1002

Texaking

