

Long Beach, CA 90808 Tel. 310-900-1000 Fax. 310-900-1077 www.turboairinc.com

Proi	iect	
110	ICOL	٠

Model # : Item # :

Available W/H :

Approval :

Swing Door Freezers

____ FEATURES & BENEFITS =___

Self-Cleaning Condenser

The accumulation of dust in the condenser can cause the failure or breakdown of refrigerators. Refrigerators run normally until they reach a certain level of accumulation. At some point, when they are over the limit, their performance drops quickly resulting in damage to, or disposal of the stored products inside. The Self-Cleaning Condenser device keeps the condenser clean and prevents system failure by automatically brushing daily.

Digital temperature control & monitor system

- · Keep food products safe by maintaining constant temperatures. • Alarms that sound when doors are not sealed shut; protect against food spoilage that originates from cold air leaks.
- · Early Warning Alarm program detects issues before malfunction occurs.
- Digital display allows for easy monitoring.
- Programs interpret the condition of refrigeration systems by self-diagnosis.
- Rapid cool-down function (Turbo Freeze)
- Smart defrost system will defrost as needed.
- · Automatic evaporator fan motor delays.

Hydrocarbon refrigerants (R-290)

With innovative and eco-friendly technology, Turbo Air brings you hydrocarbon refrigerators designed to meet DOE's Energy Conservation Standards in 2017 and to use EPA's SNAP Program approved HC refrigerants. Hydrocarbon refrigerants do not deplete the ozone layer and have very low contribution to global warming (ODP-0, GWP-3).

Energy conserving fan control

Utilizing algorithmic air circulation for optimal temperature levels, our innovative fan control system conserves energy by at least 15% and increases compressor life by up to 30%.

Individual two cycle refrigeration systems

No electrical cabinet heater is needed

Turbo Air is the first in the industry to replace a frame heater with a method of using compressor-produced heat. This eliminates any unnecessary energy consumption while providing efficient freezing performance.

High-density polyurethane insulation

The entire cabinet structure is foamed-in-place using high density, CFC free polyurethane insulation.

Triple pane heated glass doors

Equipped with unique triple-pane heated glass doors which enhance energy efficiency by preventing heat transfers and minimizing condensation. Lightweight door construction reduces door maintenance, bushing wear, and facilitates smooth door opening.

CU./FT.

62.2

#of

Shelves

12

HP

 $2/3 \ge 2$

LED lighting interior

Freezer holds -10°F ~ 5°F for the best in frozen food preservation

Swing

Door

3

Glass Door Merchandisers Super Deluxe Series

Qty :

Model : TGF-72SDH*-N



TGF-72SDHB-N

Patented Self-Cleaning Condenser



This product is equipped with a fine mesh filter to the front of the condenser to catch dust, and a rotating brush that moves up and down daily to remove excess buildup outward and away.

78 x 311/2 x 77

	gerant	SPEC ISO 9001:2008	و Inte	us ertek	Intertek	3 YEAR	Compressor 7 YEAR WARRANTY (U.S.A enly)
AMPS	Crated Weight (1bs.))		L	x D [*] x (inches)	H^{\dagger}

915

Model

TGF-72SDH*-N

13.6 *Depth does not include 2-1/4" (57mm) for door handle. † Height does not include 2-1/2" (63mm) for leg height. # White cabinet (W), Black cabinet (B).

Swing Door Freezers

Model : TGF-72SDH*-N

ELECTRICAL DATA				
Voltage	115/60/1			
Plug Type	• NEMA 5-20P			
Full Load Amperes	13.6			
Compressor HP	2/3 x 2			
Cord Length (ft.)	7			
Refrigerant	R-290			
DIMENSIONAL DATA				
# of Doors	3			
Net Capacity (cu. ft.)	62.2			
Ext. Length Overall (in.)	78 (1981mm)			
Ext. Depth Overall (in.)*	311/2 (799mm)			
Ext. Height Overall (in.) [†]	77 (1956mm)			
Int. Length Overall (in.)	74 (1880mm)			
Int. Depth Overall (in.)	243/8 (618mm)			
Int. Height Overall (in.)	511/2 (1307mm)			
# of Shelves	12			
Shelf Size (L x D) (in.)	223/4 x 233/4 (Left/Right)			
	243/4 x 233/4 (Middle)			
Net Weight (lbs.)	818			
Gross Weight (lbs.)	915			

Design and specifications subject to change without notice.

Actual shipping weight may differ due to extra packing materials for product protection. * Depth does not include 2-1/4" (57mm) for door handle.

+ Height does not include 2-1/2" (63mm) for leg height.


WARRANTY: ³ Year Parts and Labor Warranty Additional 4 Year Warranty on Compressor


STANDARD FEATURES

- Anti-corrosion coated evaporator
- Adjustable PE (polyethylene) coated wire shelves
- Door locks standard
- * Two color options available (standard): white cabinet (W), black cabinet with black color trim (B).

OPTIONAL ACCESSORIES

- 4" casters, 1/2" diameter & 13 TPI: G8F6500101 (non-brake), G8F6500201 (w/ brake)
- Additional PE coated wire shelf: P0178K0100 (Left), P0178K0300 (Middle), P0178K0200 (Right)
- Price tag channel: P0122K5600 (Left & Right, 21"L), P0122K5400 (Middle, 21-1/2"L)





Ver.20200819



(GERMAN)

KNIFE

Turbo Air : 800-627-0032 **GK** : 800-500-3519

Turbo air Texaking

■ Warranty : 800-381-7770 ■ AC : 888-900-1002

