HEATED HOLDING

VULCAN



Model VBP15



UL Listed. UL Listed to Canadian safety standards. Classified by UL to NSF Standard #4.

SPECIFICATIONS

Vulcan Model No. VBP heated holding and transport cabinets. Blower motor for gentle and even temperature distribution. Complete with 5" heavy duty casters (2 swivel with brakes and 2 rigid) (VBP5 has 3" casters). Simple knob actuated electronic control with digital display for holding at temperatures up to 190°F. Adjustable racking will hold 18" x 26" or 12" x 20" pans or a combination of both on 11/2" centers. Lip-load racking will hold 18" x 26" pans on 11/2" centers. Shelving will hold a variety of pan sizes. Complete with universal tray slides adjustable on 11/2" centers. Cabinet interior and exterior are both constructed out of 20 gauge stainless steel. Recessed side-mounted handles, magnetic action door latch, and full insulation; 11/2" in side walls and 2" in top. Integrated steel frame for maximum strength. Field reversible doors. Complete with rear mounted cord and plug: NEMA 5-15 for 120 volts and NEMA 6-15 for 208-240 volts. One year limited parts and labor warranty. After the first year, 10-year parts warranty on the heating elements.

VBP SERIES HOLDING & TRANSPORT CABINETS

Item #

Units with adjustable racking:

□ VBP5 □ VBP7	(see reverse for capacities) (see reverse for capacities)					
	(see reverse for capacities)					
U VBP15	(see reverse for capacities)					
D VBP18	(see reverse for capacities)					
Units with lip-load racking:						
	(Fifteen 18" x 26" x 1" sheet pans)					
VBP15LL	(Thirty 18" x 26" x 1" sheet pans)					
Units with shelve	S:					
VBP7SL	(Three Shelves)					
VBP15SL	(Six Shelves)					
STANDARD FEATURES						
Holding Capa	city:					

- Holding Capacity:
 - 18" x 26" sheet pans.
 - 12" x 20" pans, or a combination of both on $11/_2$ " centers.
- Other pan sizes on shelves.
- Simple knob actuated electronic control with digital display for holding at temperatures of up to 190°F.
- Blower motor for gentle and even temperature distribution.
- Dutch doors (VBP15 and VBP18).
- 5" heavy duty casters (2 swivel with brakes and 2 rigid) (3" on VBP5).
- Recessed side mounted handles.
- Universal tray slides adjustable on 1¹/₂" centers.
 VBP15 & VBP13 ship with 10 pairs of tray slides. VBP7 & VBP5 ships with 5 pairs, VBP18 ships with 15 pairs.
- Interior and the exterior are both constructed out of 20 gauge stainless steel.
- Fully insulated with 11/2" in side walls and 2" in top.
- Integrated steel frame for maximum strength.
- Magnetic action door latch.
- Field reversible doors.
- Rear mounted cord.
- Complete with cord and plug: NEMA 5-15 for 120 volts and NEMA 6-15 for 208-240 volts.
- One year limited parts and labor warranty. After the first year, 10-year parts warranty on the heating elements.

OPTIONS


- □ 208/240 volt
- □ Humidity pan
- □ Full perimeter bumper
- Glass Dutch doors (VBP7 and VBP15 only)
- □ Wire shelves to sit on tray slides
- □ Additional tray slides
- Mechanical control



HEATED HOLDING

VULCAN

VBP SERIES HOLDING & TRANSPORT CABINETS



VBP13 Front & Side Views

N

VBP15 & VBP18 Front & Side Views

MODEL	DIMENSIONS	CAPACITY		ELECTRICAL			SHIPPING WEIGHTS	
	EXTERIOR	12" x 20" x 2½" PANS	18" x 26" SHEET PANS	VOLTS	WATTS	AMPS	LBS	KG
VBP5	271⁄4" W x 33" D x 301⁄2" H	10	5	120	1,500	12.5	173	79
VBP7	27¼" W x 33" D x 39" H	14	7	120	1,500	12.5	198	90
VBP7LL	27¼" W x 33" D x 39" H	NA	15	120	1,500	12.5	198	90
VBP7SL	27¼" W x 33" D x 39" H	Unit comes with 3 shelves		120	1,500	12.5	198	90
VBP13	27¼" W x 33" D x 59¾" H	26	13	120	1,500	12.5	270	123
VBP15	27¼" W x 33" D x 65¼" H	30	15	120	1,500	12.5	297	135
VBP15LL	27¼" W x 33" D x 65¼" H	NA	30	120	1,500	12.5	297	135
VBP15SL	27¼" W x 33" D x 65¼" H	Unit comes with 6 shelves		120	1,500	12.5	297	135
VBP18	271⁄4" W x 33" D x 731⁄2" H	36	18	120	1,500	12.5	337	153

*per compartment

Optional bumper adds $3^{1}/4$ " to the width and $1^{5}/8$ " to the depth.



P.O. Box 696
Louisville, KY 40201
Toll-free: 1-800-814-2028
Local: 502-778-2791
Quote & Order Fax: 1-800-444-0602

NOTE: In line with its policy to continually improve its products, Vulcan reserves the right to change materials and specifications without notice.