GRIDDLES & BROILERS

VULCAN



Model VHP636



SPECIFICATIONS

Exterior Dimensions:

_____" wide x 31³/₈" deep x 12" working height

CSA Design Certified. NSF Certified.

SPECIFY TYPE OF GAS WHEN ORDERING. SPECIFY ALTITUDE WHEN ABOVE 3,999 FT.

VHP SERIES HEAVY DUTY GAS HOT PLATE

- □ VHP212 12" wide
- □ **VHP424** 24" wide
- □ **VHP636** 36" wide
- □ VHP848 48" wide
- □ VHP212U 12" wide with 4" elevated rear step-up burners
- □ VHP424U 24" wide with 4" elevated rear step-up burners
- □ VHP636U 36" wide with 4" elevated rear step-up burners
- **VHP848U** 48" wide with 4" elevated rear step-up burners

STANDARD FEATURES

- Stainless steel sides, control panel, top trim and backsplash.
- Full width pull out crumb tray.
- Heavy duty cast iron top grates.
- 30,000 BTU/hr. (27,500 BTU/hr. for LP gas) open burners with lift-off heads.
- Standing pilot ignition system.
- One infinite heat control valve for each burner.
- 4" adjustable legs.
- \blacksquare ³/₄" NPT rear gas connection and gas pressure regulator.
- One year limited parts and labor warranty.

OPTIONS

- Cutting board.
- Condiment rail.
- Plate rail.
- □ Stainless steel stand with undershelf and casters.



a division of ITW Food Equipment Group LLC

VULCAN

VHP SERIES HEAVY DUTY GAS HOT PLATE

INSTALLATION REQUIREMENTS:

- 1. A gas pressure regulator supplied with the unit must be installed. Natural Gas 5.0" (127 mm) W.C. Propane Gas 10.0" (254 mm) W.C.
- 2. An adequate ventilation system is required for commercial cooking equipment. Information may be obtained by writing to the National Fire Protection Association, 1 Batterymarch Park, Quicy, MA 02169, www.NFPA.org. When writing refer to NFPA No. 96.
- 3. These units are manufactured for installation in accordance with National Fuel Gas Code, ANSI-Z223.1/NFPA #54 (latest edition). Copies may be obtained from The American Gas Association Accredited Standards Committee Z223, @ 400 N. Capital St. NW,


Washington, DC 20001, or the Secretary Standards Council, NFPA, 1 Batterymarch Park Quincy, MA 02169-7471.


NOTE: In the Commonwealth of Massachusetts


All gas appliances vented through a ventilation hood or exhaust system equipped with a damper or with a power means of exhaust shall comply with 248 CMR.


4. Equipment clearance	e: Non-Combustibles	Combustibles	
	Sides Back	Sides Back	
Standard	0" 0"	13" 6"	
Step-Up	0" 0"	13" 9"	

5. This appliance is intended for commercial installation only and is not intended for home use.









MODEL	WIDTH	DEPTH	OVERALL HEIGHT*	WORKING HEIGHT*	NO. OF BURNERS	TOTAL BTU/HR. NATURAL GAS	TOTAL BTU/HR. PROPANE GAS	APPROX SHIP WT. (LB/KG)
VHP212	12"	313⁄8"	165⁄8"	12"	2	60,000	55,000	95 lbs./43 kg
VHP424	24"				4	120,000	110,000	165 lbs./74 kg
VHP636	36"				6	180,000	165,000	265 lbs./119 kg
VHP848	48"				8	240,000	220,000	310 lbs./140 kg

*These are nominal dimensions and can vary by +1.75" with adjustable legs.



P.O. Box 696 Louisville, KY 40201 Toll-free: 1-800-814-2028 Local: 502-778-2791 Quote & Order Fax: 1-800-444-0602

F38336 (09/20)