



“WE MAKE THE KITCHEN BETTER!”

ATOSA USA, INC.

Toll Free: 855-855-0399 Email: info@atosausa.com

www.atosa.com | www.atosausa.com

California, Colorado, Florida, Georgia, Illinois, New Jersey, Ohio, Texas, Washington

Refrigerated Chef Bases

Standard Features

- Stainless steel exterior and interior
- Stainless steel pans included
- Electronic temperature controller
- Maintains temperatures between 35°F – 38°F
- Heavy duty compressor with environmentally friendly R290 refrigerant
- Heavy duty stainless steel drawer slides and rollers
- Magnetic drawer gaskets
- Recessed door handles
- Pre-installed casters
- One-piece heavy duty reinforced stainless steel top to support counter top equipment
- Corner guards included
- Pull out handles included

For the best results of food preservation we recommend setting your refrigerator between 35°F to 38 °F

1. Don't forget to leave the unit some room to breathe!
2. Please clean the condenser frequently to give the unit more fresh air.

MODELS:

MGF8448GR / MGF8450GR / MGF8451GR
MGF8452GR / MGF8453GR / MGF8454GR



MGF8448GR



MGF8450GR



MGF8451GR



MGF8452GR



MGF8453GR



MGF8454GR



2 YEAR PARTS AND LABOR WARRANTY
5 YEAR COMPRESSOR PART WARRANTY





"WE MAKE THE KITCHEN BETTER!"

ATOSA USA, INC.

Toll Free: 855-855-0399 Email: info@atosausa.com

www.atosa.com | www.atosausa.com

California, Colorado, Florida, Georgia, Illinois,

New Jersey, Ohio, Texas, Washington

SPECIFICATIONS

Models	Door	Capacity (Cu.Ft.)	Pans per unit	Casters (inch)	Rated Current (A)	Voltage (V/Hz/Ph)	HP	Refrigerant	Exterior Dimensions (inch)	Net Weight (lb)	Gross Weight (lb)
MGF8448GR	2	4.7	2*12x20 & 6*1/6	5	2.3	115/60/1	1/7	R290	35 ^{9/16} ×33×26 ^{3/5}	170	218
MGF8450GR	2	7.7	4*12x20 & 6*1/6	5	2.3	115/60/1	1/7	R290	48 ^{2/5} ×33×26 ^{3/5}	220	258
MGF8451GR	2	8.4	6*12x20	5	2.3	115/60/1	1/7	R290	52×33×26 ^{3/5}	229	273
MGF8452GR	4	8.4	6*12x20	5	2.3	115/60/1	1/7	R290	60 ^{1/2} ×33×26 ^{3/5}	234	282
MGF8453GR	4	12.1	8*12x20	5	2.3	115/60/1	1/7	R290	72 ^{1/2} ×33×26 ^{3/5}	300	364
MGF8454GR	4	12.1	8*12x20	5	2.3	115/60/1	1/7	R290	76×33×26 ^{3/5}	309	368

PLAN VIEW

